

Shakers VXR basic IKA-Vibrax®, IKA®

Shaker VXR basic IKA-Vibrax®

Optoelectronically controlled small shaker with a very wide speed range suitable for continuous operation. New design with improved drive system. Circular shaking motion and slow speeds are well maintained.

Attachments for the basic unit are interchangeable.

Technical data:

External (W × D × H):	157 × 247 × 130 mm
Weight:	5,7 kg
Power supply:	230 V, 50/60 Hz
Motor rating input/output:	35/13,2 W
Motion:	horizontal orbital
Orbital:	4 mm Ø
Speed range:	0 to 2200 min ⁻¹ , infinitely adjustable

Article	Order No.
① Shaker VXR basic IKA-Vibrax®	52 36 19000

Accessories

Article	Order No.
② One-hand attachment VX 1 for shaking single non-fixed vessels from 1 to 250 ml Dimensions (W × D × H): 130 × 135 × 40 mm	52 36 13120
③ Test tube attachment VX 2 for up to 36 test tubes or centrifuge tubes with 16 mm Ø, material: Makrolon Dimensions (W × D × H): 140 × 145 × 115 mm	52 36 13121
④ Universal attachment VX 8 for fast and secure clamping of e.g. Erlenmeyer flasks up to 500 ml Dimensions (W × D × H): 265 × 136 × 60 mm	52 36 10400
⑤ Eppendorf attachment VX 2 E for intensive shaking of up to 64 Eppendorf tubes (1.5 ml)	52 36 16181
⑥ Attachment VX 7 for gentle shaking of culture flasks, petri dishes etc.	52 36 95330

