

Safety Cabinets, Köttermann

Safety cabinets for storing combustibles

Köttermann safety cabinets are intended to protect people in case of a fire. The insulating sandwich design of the cabinet protects the hazardous materials stored in it against heat and flames. This means that the spontaneous combustion of flammable fluids is ruled out; the employees have sufficient time to seek shelter.

For proper storage of combustible hazardous materials pursuant to TRbF 20 Enclosure L.

- Material: galvanized and epoxy-coated steel
- Flame resistance: 90 minutes (type 90) certified pursuant to EN 14470-1

Tall safety cabinets

Equipment:

- Easy-moving, corrosion-protected door lock
- Height levelling
- Earth connection
- 1 floor pan with perforated plate insert
- Doors lockable
- Exhaust connection (DN 75) with fire trap
- Optional as ErgoPlus, with one-hand operation and time-delayed door lock

	W x H x D mm	Equipment	Order No.
①	600x1955x615	1 hinged door right, 4 pull-outs, autom. door closing	10 12 03722
	900x1955x615	2 hinged doors, 4 pull-outs, autom. door closing	10 12 03723
②	1200x1955x615	2 hinged doors, 4 pull-outs, autom. door closing	10 12 03724
	600x1955x615	1 hinged door right, 3 shelves, drip cup	10 12 03702
	900x1955x615	2 hinged doors, 3 shelves, drip cup	10 12 03703
	1200x1955x615	2 hinged doors, 3 shelves, drip cup	10 12 03705

Underbench safety cabinets

Equipment:

- Earth connection
- Floor pan with perforated steel insert
- Doors and extractions lockable
- Steel socket with integrated floor suction
- Exhaust connection (DN 75) with fire trap

	W x H x D mm	Equipment	Order No.
	592x720x570	1 pull-out	10 12 03715
	890x720x570	1 pull-out	10 12 03716
③	1100x720x570	2 hinged doors, drip cup	10 12 03717
	1100x720x570	2 pull-outs	10 12 03718
④	1400x720x570	2 hinged doors, 1 pull-out, drip cup	10 12 03719
	1400x720x570	2 pull-outs	10 12 03720

