

Electrical Lift „Lift 240“, BOCHEM



WWQ7J087

Electrical lab jack of compact design!

The „Lift 240“ comes with motor and control system integrated in the lab jack. Ensuring an absolutely stable stand and wobble-free lifting and lowering, it offers perfect safety. The extremely robust, highly precise scissor technology of 18/10 steel and the electronic components are durably protected using a bellows of chemically resistant PTFE.

The design of the electrical „Lift 240“ is identical with that of the mechanical 240 × 240 mm BOCHEM lab jack. Both variants can be used and replaced in existing structures. An end stop can be manually adjusted at the outside.

Technical data:

Dimensions, retracted (L×W×H):	240 × 240 × 120 mm
Max. height:	300 mm
Workspace (L×W):	240 × 240 mm
Weight:	6 kg
Lifting speed:	180 mm/min
Max. lifting of scissor:	180 mm
Max. load capacity (dynamic):	25 kg
Nominal torque:	8 Nm
Degree of protection:	IP 30
Supply voltage transformer:	100–240 VAC, 50/60 Hz
Output:	24 V
Battery remote control:	3 V, lithium cell CR2430
Permissible ambient temperature:	5 to 45°C
Noise emission:	less than 40 dB (A)
Material work space:	18/10 stainless steel
Material body:	18/10 stainless steel
Material corrugated bellows:	PUR



Article	Remote control	Order No.
① Electrical lift „Lift 240“	incl.	10 05 11220
② Remote control for „Lift 240“ (spare part)		10 05 11230

