

SONOREX TECHNIK ultrasonic baths

Devices available in different versions.

Type „H“ with heating 30 – 80°C (on request).

Type „U“ with ultrasonic or as rinsing tank without heat and ultrasound (on request).

Type „UH“ ultrasonic with heating.

Built-in ultrasonic generator. Types of series RM 16.2 to 75.2 with inclined tank floor.

Frequency: 40 kHz, RM 110 and above alternatively 25 kHz

Mains: RM 16.2 UH-RM 75.2 UH 230 V~ (±10%), 50–60 Hz

RM 110 UH-RM 210 UH 400 V~ (±10%), 50–60 Hz

Cekon connector 16 A

Welded tank, 2 mm stainless steel, 1.4404

Overflow pocket. Drain. Timer 1 – 15 min or continuous operation.

Type	Inner L x W x D mm	Ultrasonic max. out- put W	Ultrasonic nominal power W	Work. fill qty l	Hea- ting cap. W	Order No.
RM 16.2 UH	325x275x200/210 ¹⁾	1200	1 x 300	13.0	800	96 07 38200
RM 40.2 UH	480x300x300/315 ¹⁾	2000	1 x 500	30.0	1250	96 07 38210
RM 75.2 UH	580x500x300/315 ¹⁾	4000	1 x 1000	60.0	1950	96 07 38220
RM 110 UH	600x450x450	4000	1 x 1000	110.0	4800	96 07 38230
RM 180 UH	1000x500x400	2 x 4000	2 x 1000	160.0	7200	96 07 38250
RM 210 UH	750x650x500	2 x 4000	2 x 1000	210.0	7200	96 07 38270

¹⁾ inclined tank floor

Ultrasonic max. output corresponds to four times higher value of the ultrasonic nominal power


Accessories for SONOREX TECHNIK ultrasonic baths
Insert baskets made from stainless steel

Type	fits	Order No.
MK 16 B	RM 16.2 UH	96 07 38420
MK 40 B	RM 40.2 UH	96 07 38421
MK 75 B	RM 75.2 UH	96 07 38422
MK 110	RM 110 UH, RM 112 UH, ZM 112 UHL	96 07 38423
MK 180	RM 180 UH, RM 182 UH, ZM 182 UHL	96 07 38424
MK 210	RM 210 UH, RM 212 UH, ZM 212 UHL	96 07 38425

Stainless steel covers

Type	fits	Order No.
MD 16	RM 16.2 UH	96 07 38440
MD 40	RM 40.2 UH	96 07 38442
MD 75	RM 75.2 UH	96 07 38444
MD 110	RM 110 UH, RM 112 UH, ZM 112 UHL	96 07 38446
MD 180	RM 180 UH, RM 182 UH, ZM 182 UHL	96 07 38447
MD 210	RM 210 UH, RM 212 UH, ZM 212 UHL	96 07 38448