

BOLA GL 2- and 3-Way Stopcocks, Bohlender

T-shaped bore and three connections with GL thread. Cylindrical stopcock plug for good tightness, stop valve with mark of flow direction. Suitable for pressure up to max. 6 bar, or for vacuum. Universal chemical resistance, the flowing product is only exposed to PTFE.

For distributing liquids or gases. Quick and easy disconnection of flow. Connection of tubing or tubes by means of BOLA Laboratory Screw Joints

Technical data:

Material: PTFE
 Temperature resistance: from -30°C to +150°C
 Chemical resistance: +++ universal
 Pressure: 6 bar
 Vacuum: suitable

	Type	Bore shape stopcock	Bore Ø mm	Connection thread GL	Outer dimensions L x D x H mm	Order No.
①	2-way	I	4	14	54x20x38	24 17 68414
	2-way	I	6	18	64x30x45	24 17 68418
	2-way	I	8	25	78x40x57	24 17 68425
②	3-way	L	4	14	64x47x43	24 17 68614
	3-way	L	6	18	74x57x57	24 17 68618
	3-way	L	6	25	78x59x57	24 17 68625
③	3-way	T	4	14	74x57x57	24 17 68814
	3-way	T	4	18	74x57x57	24 17 68818
	3-way	T	6	25	88x69x57	24 17 68825

