

Pipette Controllers VITLAB pipeo®, VITLAB

For all pipettes from 0.1 to 200 ml. With the VITLAB pipeo® pipette controller, pipette handling is simple and comfortable. The ergonomic handle – very light weight at about 190 grams – and excellent balance all contribute to ease of operation. The speed can be adjusted easily, continuously and exactly with one hand using two buttons. A 50 ml pipette can be filled comfortably in less than ten seconds. The liquid release can be done either by gravity delivery when calibrated „Ex“ (to deliver), or in blow out mode using the battery-operated motor.

Pipettes are held securely and tightly in the exchangeable adapter. Liquid vapours are purged directly to protect the instrument.

The charge level of the recyclable battery is shown by a LED indicator. Defective batteries are easily replaced. To avoid surprises, the LED indicator changes from green to red two hours before the battery must be recharged. The VITLAB pipeo® can still be operated while the battery is being recharged.

CE marking pursuant to EU Directives 2004/108/EC, 93/68/EEC; 73/23/EEC, 93/68/EEC.

Included in delivery:

VITLAB pipeo®, battery charger (100–240 V, 50/60 Hz), 4 plug adapters (EU, UK, US/J, AUS), battery, battery compartment cover, two replacement 0.2 µm membrane filters and instruction manual.

Article	Order No.
Pipette controller VITLAB pipeo®	10 85 31501

