

Heating and Cooling Thermostats Alpha, LAUDA

LAUDA Alpha is the cost-effective choice in the area of high-quality LAUDA thermostats in the temperature range from -25 up to 100 °C. The thermostats are suitable for operation with non-flammable liquids (water, water/glycol) and for both internal and external thermostating tasks.

- 3-keys operation with large and brilliant LED display. Resolution of indication of 0.1°C
- Pressure pump with 0.2 bar pressure and 15 l/min pump flow
- Pump reduction for reducing the flow rate from 15 to 5 l/min as standard
- Temperature range from 25 to 100°C and temperature stability of $\pm 0,05$ K
- Integrated timer function for automatic shut-down of the device
- 1-point calibration can be performed by the user
- Safety functions such as alarms, warnings and malfunctions are indicated on the LED display

Immersion Thermostat

Type	Temp. range °C	Heating cap. kW	Pump pressure bar	Flow rate l/min	Order No.
A	25 – 100	1.5	0.2	15	10 23 30226

Heating thermostats

Type	Temp. range °C	Heating cap. kW	Bath vol. l	Bath opening W x D mm	Bath depth mm	Order No.
A 6	25 – 100	1.5	2.5 – 5.5	145x161	150	10 23 30733
A 12	25 – 100	1.5	8 – 12	235x161	200	10 23 30734
A 24	25 – 100	1.5	18 – 25	295x374	200	10 23 30735

Accessories for immersion and heating thermostats

Article	Order No.
Pump circulation set	10 23 32005
Cooling coil	10 23 32004

Accessoires for heating thermostats

Article	Order No.
Bath cover set A 6	10 23 33006
Bath cover set A 12	10 23 33007
Bath cover set A 24	10 23 33008

Cooling thermostats

Type	Temp. range °C	Heating cap. kW	Cooler power kW	Bath vol. l	Bath opening WxD mm	Bath depth mm	Order No.
RA 8	-25 – 100	1.5	0,225	5 – 7.5	165x190	160	10 23 31907
RA 12	-25 – 100	1.5	0,325	9.9 – 14.5	300x190	160	10 23 31908
RA 24	-25 – 100	1.5	0,425	14 – 22	350x290	160	10 23 31909



webcode  WW18A007

