

Laboratory-Pharmacy Refrigerator +2°C – +12°C, LAT



WWW4U107



Fully sealed, low-noise, high-efficiency hermetical compressor and ventilated condenser (also suitable for use in tropical regions). Forced-air cooling system designed to ensure maximum temperature stability in the fridge, even in case of frequent door opening. The evaporator fan switches off when the door is opened. CFC-free freezing agent R404a or CFC / H-CFC-free natural freezing agent R290 available on request.

Standard equipment

- Shelves
- Four one-way wheels with stabilizing adjustable feet
- Power cord with Schuko type plug or British type plug
- RFI filter
- Password protected power switch and settings
- 4.3" LCD touchscreen with alarm system
- Data Logger with USB port

Optional accessories

- Scotch-Brite stainless steel sliding drawers
- Plexiglas frontal side
- Kit of dividers for drawer
- Additional shelf
- Weekly temperature chart recorder
- Back-up battery
- GSM alarm to send SMS alarm messages
- DIN 58345 conformity
- LAN port
- Test hole (Ø 25 mm)
- Electric digital key lock

Technische Daten:

Temperature: +2°C to +12°C
Noise: 45 db

	Model	Volume l	Quantity shelves	Weight kg	Width × Depth × Height mm	Order No.
①	SB 10	100	2	57	600×600×860	10 20 13010
②	FS 15	150	2	73	600×600×1360	10 20 13015
	FS 20	200	3	82	600×600×1560	10 20 13020
	FS 25	250	4	88	600×600×1760	10 20 13025
③	FS 30	300	5	97	600×600×1960	10 20 13030

Special sizes of up to 1,400 litres are available as well. Accessories available on request, please contact us.



①



②



③

