

Benchtop Centrifuge ROTOFIX 32 A, HETTICH

Benchtop centrifuge ROTOFIX 32 A

For decades, the ROTOFIX 32 A has set the standard in daily lab routine thanks to its versatility and solid construction. The benchtop centrifuge spins sample volumes up to 6 x 94 ml, 40 blood collection tubes or 8 x 50 ml conical tubes with a simple user interface. Hettich's cytology rotors are compatible with the cyto-systems by most competitors and have bio-containment lids.

Technical data:

External dimensions (WxDxH): 366 x 430 x 257 mm
Weight: approx. 23 kg
Power supply: 208 – 240 V, 50/60 Hz
Connected load: 300 VA
Max. speed: 6000 min⁻¹
Max. RCF: 4226
Max. capacity: 4 x 100 ml / 6 x 94 ml
Emission/Immunity: EN/IEC 61326-1, class B

Article	Order No.
① ROTOFIX 32 A, benchtop centrifuge without rotor	10 56 11206

Accessories

Article	Order No.
② Swig-out rotor 1624, without suspension gear for max. 4 x 100 ml or 4 slide samples, max. RCF 2665	55 56 11624
Round bucket 1398, alloy, 50 ml, fits in rotor 1324	10 56 11398
Round bucket 1490, alloy, 100 ml, fits in rotor 1324	10 56 11490
Round bucket 1481, alloy, 100 ml, fits in rotor 1624	10 56 11481
Lid for bucket 1481, 1495 and 1490, with biocontainment	10 56 11492
③ Swing-bucket rotor 1324 for max. 4 x 100 ml, without suspension gear	10 56 11324
④ Fixed-angle rotor for max. 6 x 94 ml	10 56 11620

Supplied without the illustrated accessories. More rotors and accessories on request.

