

Safety Underbench Cabinets, asecos

Suitable for placement under fume hoods.

Proper storage of hazardous substances in work areas in compliance with TRGS 510 (Appendix 3). Type-tested to withstand fire for 90 minutes as defined in EN 14470-1 (Type 90). GS-approved, in conformity with CE.

Expansion joints provide protection in case of fire. Fine sheet steel outer shell with plastic coating, light gray (RAL 7035). Plastic coating with good chemical, impact and scratch resistance characteristics applied to inner surface. Edge protection on insulation material. External ground connection.

Model UB90.060.110.S

- one drawer, can be locked in any position
- useable internal height (without perforated insert): 465 mm

Standard equipment:

- integrated collecting pan acc. to StawaR
- open drawer closes in case of fire (thermal activation)
- Ground cable with clamp in the drawer.

Technical data:

External dimensions (W × D × H): approx. 1102 × 574 × 600 mm
 Collecting pan (W × D × H): approx. 930 × 440 × 85 mm
 Drawer load capacity (distributed load): 50 kg



① ②



③ ④



⑤ ⑥

Article	Order No.
① Safety cabinet UB90.060.110.S with collecting pan	91 13 56011
Delivery costs depending on place of delivery	

② Interior equipment versions model VBF.60.110-S

Article	Order No.
Perforated plate insert (stainless steel 1.4301)	10 13 13424
2nd drawer level (powder-coated steel plate)	91 13 18053

Model UB90.060.110.2S

- with two drawers
- useable internal height per drawer (without perforated insert): 465 mm

Standard equipment:

- integrated collecting pan acc. to StawaR in each drawer
- open drawer closes in case of fire (thermal activation)
- ground cable with clamp in the drawer.

Technical data:

External dimensions (W × D × H): approx. 1102 × 574 × 600 mm
 Collecting pan (W × D × H): approx. 425 × 440 × 85 mm
 Drawer load capacity (distributed load): 50 kg

Article	Order No.
③ Safety cabinet UB90.060.110.2S with collecting pans	10 13 13427
Delivery costs depending on place of delivery	

④ Interior equipment versions model UB90.060.110.2S

Article	Order No.
Perforated plate insert (stainless steel 1.4301), left or right drawer	10 13 19975
2nd drawer level (powder-coated steel plate), left or right drawer	10 13 13407

Model UB90.060.110.2T

- with double wing doors
- usable inner height (collection tray with perforated metal insert): 400 mm

Standard equipment:

- Doors close automatically in case of fire (thermal activation)

Technical data:

External dimensions (W × D × H): approx. 1102 × 574 × 600 mm

Interior equipment (W × D × H)

Tray: 969 × 416 × 20 mm
 Perforated plate insert: 955 × 425 × 60 mm
 Bottom collecting pan: 959 × 426 × 75 mm

Article	Order No.
⑤ Safety cabinet UB90.060.110.2T without interior equipment	10 13 13443
Delivery costs depending on place of delivery	

Interior equipment packages model UB90.060.110.2T

(powder-coated steel plate)

Recommended configuration: perforated plate insert and bottom collecting pan acc. to StawaR

Article	Order No.
⑥ Perforated plate insert, bottom collecting pan acc. to StawaR	10 13 13447
Tray, perforated plate insert, bottom collecting pan acc. to StawaR	10 13 13453

